

DTU-1141



The DTU-1141 provides an ideal document viewing and signing experience with its 10.6-inch, full HD resolution screen, minimal footprint and thin profile. It operates as an external monitor, but utilizes Wacom's patented pen technology to provide input for writing and signing. It is perfect for business applications that benefit from people working directly on screen with a pen, such as presenting forms for customers to review and sign electronically, or marking up and annotating documents. While not in use for signing, it can display slideshows or advertising videos.

The ability to perform secure transactions is the strength of the DTU-1141. It includes state-of-the-art encryption, and unique hardware ID (UID) to pinpoint the exact unit used for any digital signature.

Signature Accuracy

The pen display's high sensor resolution and pressure levels produce a clear and true-to-life electronic signature.

100% Hand Rejection

Electromagnetic resonance (EMR) is used to capture the movements of the pen, not accidental touches by the hand or finger. EMR ensures that only the intended signature is captured.

User Acceptance

The ability to see your signature as it is captured provides an intuitive signing experience.

Lower Cost of Ownership

A durable signing surface and Wacom's cordless, battery-free pen technology contribute to a lower total cost of ownership.

- 10.6" IPS LCD boasts full color, full HD resolution (1920x1080) and wide viewing angle. Supports multiple resolutions from 800x600 to 1920x1080.
- Large screen is ideal for showing promotional materials when not used for signing.
- Single USB cable installation. USB cable supplies video, power and USB data.
- Patented, cordless, battery-free pen with 1024 levels of pressure sensitivity for premium signing/writing experience.
- State-of-the-art encryption to ensure secure transactions.
- Integrated stand supports use either flat on the desktop or at a 15° angle.
- 4 capacitive-touch ExpressKeys can be assigned to common functions.
- Hardened, anti-glare surface provides high durability and easier viewing in different lighting conditions.
- Unique hardware ID (UID) to identify the exact unit used for any transaction.
- Kensington® Security Slot to secure the unit when needed.
- VESA mounting holes allow you to use third-party arms and stands.

DTU-1141

General Specifications

| | |
|-----------------------------|--|
| Dimensions (W x H x D) | 11.1" x 8.3" x 0.4" (283 x 210 x 11 mm) |
| Weight | 1.54 lbs. (700 grams) |
| Stand inclination | 15° (with stand) or flat |
| Power supply | Via USB (no AC power required) |
| Power consumption | 5W maximum, 1W or less in sleep mode |
| Communication interface | USB 2.0 (for video via DisplayLink and USB data) |
| Supported operating systems | Windows® 8.1 / 8 / 7 / XP Mac OS 10.7 and later |

LCD Screen

| | |
|------------------------|--|
| Screen size (diagonal) | 10.6" (269.2 mm) |
| Aspect ratio | 16:9 |
| Display type | IPS TFT display |
| Cover glass surface | Tempered anti-glare etched glass |
| Native resolution | 1920 x 1080 |
| Supported resolutions | 800 x 600, 1024 x 600, 1024 x 768, 1280 x 800, 1440 x 900, 1920 x 1080 |
| Viewing angle (H/V) | 170°/ 170° |
| Colors | 16.7M colors |
| Luminance | 200 cd/m2 (typical) |
| Contrast ratio | 800:1 (typical), 600:1 (minimum) |

Pen and Tablet

| | |
|-----------------------|---|
| Technology | Electromagnetic Resonance (EMR) |
| Active area size | 9.3" x 5.2" (235 x 132 mm) |
| Pressure levels | 1024 |
| Coordinate resolution | 2540 lpi (0.01 mm/pt) |
| Coordinate accuracy | ±0.02 inch (±0.5 mm) center |
| Report rate | 200 pps |
| Reading height | 5 mm or more (center) |
| Encryption | AES 256 bit encryption RSA 2048 bit key exchange |

Miscellaneous

| | |
|---|--|
| Pen storage | Integrated pen compartment, pen holder |
| Mount system | VESA 75 mm |
| Software | Compatible with E-signature software, Wacom's SDKs, & Wacom's sign pro PDF |
| Drivers | Wacom driver and DisplayLink driver required |
| Operating temperature/Relative humidity | +5° to +40° C / +41° to +104° F, 30% to 80% (non-condensing) |
| Storage temperature/Relative humidity | -20° to +60° C / -4° to +140° F, 30% to 90% (non-condensing) |
| Warranty | 3 years |

